1/2" Bayonet 3-CCD Color Video Camera

KY-F32U

- **Standard 1/2" bayonet mount**
- **750 horizontal lines resolution with a high sensitivity of F 9.5 at 2,000 lux and minimum illumination of 6.0 lux**
- **Memory function**
- **Comprehensive input and output terminals**
- **High-Resolution Frame Integration Mode boosts vertical resolution to 480 lines**
- **Negative video function**
- **Full-time automatic operation**
- **Menu setup control from camera head and RS-232C**

Image pickup device:	1/2" interline CCD X 3 (R,G,B)
Variable scan:	
Output signals	
	1 V(p-p), 75 ohms BNC connector one channel, D-SUB 9-pin connector one channel
Y/C signal:	
Component signal:	
Composite sync signal:	
Remote input:	
Power requirements:	
Ambient temperature range:	
Weight:	

For 9 pin connector configuration and 9 pin signal cables, see page 44

Optional Accessories

RM-LP55U
Camera remote control unit

RM-LP57U
Camera remote control unit
(Rack mount type)

RM-713MDU
Lens remote control unit

(Fujinon)

S14x7.5BMDU
14:1 power zoom lens

YH13x7.5 BKTSU
13:1 power zoom lens

AA-P700U
AC power adaptor

VC-P893U
RS-232C interface cable

VC-P894U
RS232C interface cable for Macintosh

All model numbers, specifications and prices are subject to change without notice.