



- 40" viewable image size
- 170° horizontal/vertical viewing angle
- 1280 x 768 native resolution
- 450-nit brightness (typical)
- 600:1 contrast ratio
- Ultra-narrow 3.9" profile
- Digital/analog interface
- S-Video, Composite, VGA, DVI and Component inputs
- 60,000-hour lamp
- Picture-in-Picture and Picture-by-Picture

A versatile, high-end 40" LCD display, the Samsung SyncMaster 403T is perfect for 24/7 digital signage, status control info, retail display, video conferencing or anywhere else a large, bright, easy-to-read display is required. Its ultra-wide 170° vertical and horizontal viewing angles ensure visibility from almost any position. Its ultra-narrow 3.9" profile creates a sleek installation. And its 60,000-hour lamp delivers years of maintenance-free operation.

403T

40" Digital/Analog LCD Display



403T



40" Digital/Analog LCD Display

Specifications	
Panel	a-si TFT/PVA
Viewable Size	40"
Native Resolution (Optimum)	1280 x 768
Maximum Addressable Resolution	1600 x 1200 (UXGA) Analog Only
Pixel Pitch	0.681 mm
Brightness (Typical)	450 cd/m ²
Contrast Ratio	600:1
Colors Supported	16.7M
Viewing Angle (H/V)	170°/170°
Interface	Analog/Digital
Input Video Signal	Analog RGB, DVI Digital Link, S-Video, Component/HDTV
Sync Type	Separate H/V, Composite H/V, SOG
Input Connectors	15-Pin D-Sub, DVI-D, S-Video, BNC Connector, Component, HDTV, External Control, Audio
Horizontal Frequency, Analog	31 – 70 kHz
Horizontal Frequency, Digital	31 – 50 kHz
Vertical Frequency	55 – 85 Hz (60 Hz @ WXGA)
Bandwidth	100 MHz
Plug and Play	DDC 1/2B
Power Consumption	220 Watts Max
Emission Standard	TCO '95
Mac Compatibility	Yes
Sun Compatibility	Yes
Optional Accessories	10-Watt Multimedia Speakers, Wall Mount, Table Stand
Available Colors	Black
Dimensions (W x H x D)	With Stand: 38.3" x 26.5" x 11.6", Without Stand: 38.3" x 24.1" x 3.9"
Net Weight	58.2 Lbs.
Parts/Labor/Backlight Warranty	3/3/3 Years

SAMSUNG

Product Information
1-866-542-7214

Product Support
1-800-SAMSUNG

www.samsungusa.com/monitor

©2004 Samsung Electronics America, Inc. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies.

